

CATLINE CAT. 6A S - IE CONNECTION CABLE

Industrial Ethernet cable, suitable for cable tracks,
with mounted RJ45 connector and mounted RJ12 connector



Application: Connection cable between PC and IP cameras.

Technical Data:

Temperature range:	-20 °C to +70 °C
Connection side 1:	RJ45 connector, mounted, Cat. 6A, 8-pole with cable gland
Connection side 2:	RJ12 connector, mounted
Marking:	yellow marking tube with marking: item number - order number - length - certification mark

Cable characteristics:

SAB item no.:	L1677-4631
Dimension:	4 x 2 x 26 AWG
Conductor:	bare copper strands, fine wires
Insulation:	special polymer
Screen:	alu foil and tinned copper braiding
Outer sheath:	PUR, green (similar RAL 6018)
Outer diameter:	approx. 7,1 mm
Approvals:	UL/CSA
Oil resistance:	TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Min. bending radius	
<i>flexible application:</i>	5 x d
<i>continuously flexible:</i>	15 x d

item no. with length code

length	item no.: S1677-4044- _ _ _ _ _
0,5 m	00050
1,0 m	00100
2,0 m	00200
3,0 m	00300
5,0 m	00500
7,5 m	00750
10,0 m	01000

