

# CABLE TRACK CABLES

## SD 200 Extremely flexible TPE/PUR data cable with coloured cores for continuous movement



Marking for SD 200 07742501:

SAB BRÖCKSKES · D-VIERSEN · SD 200 25 x 0,14 mm² CE

### Construction:

<b>Conductor:</b>	bare copper strands, extra fine wires
<b>Insulation:</b>	TPE
<b>Colour code:</b>	with reference to DIN 47100
<b>Stranding:</b>	specially adjusted layering with non-woven tape over each layer
<b>Wrapping:</b>	non-woven tape
<b>Sheath material:</b>	PUR, TPU acc. to DIN VDE 0282 part 10 + HD 22.10 with mat surface
<b>Sheath colour:</b>	grey (RAL 7032)

### Outstanding features:

- **labs uncritical**  
(labs = enamel moisturing interfering substances)
- **flexible at low temperatures**
- **halogen-free**
- **travel > 10 m is possible**
- **high abrasion resistance**
- **min. bending radius**
- **small outer diameter**
- **EAC approval**

### Technical data:

<b>Peak operating voltage:</b>	max. 350 V acc. to DIN VDE
<b>Testing voltage U:</b>	1500 V acc. to DIN VDE 0472 part 509
<b>Min. bending radius</b> <i>continuously flexible:</i>	7,5 x d
<b>Radiation resistance:</b>	5 x 10 <sup>7</sup> cJ/kg
<b>Temperature range</b> <i>fixed laying:</i> <i>flexible application:</i>	-50/+90 °C -40/+90 °C
<b>Halogen-free:</b>	acc. to DIN VDE 0472 part 815 + IEC 60754-1
<b>Oil resistance:</b>	very good - TPU acc. to DIN VDE 0282 part 10 + HD 22.10
<b>Chem. resistance:</b>	good against acids, alkalines, solvents, hydraulic liquids etc.
<b>Continuous flexibility:</b>	very good
<b>Weather resistance:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
07740201	2 x 0,14	0,11	3,2	2,7	11
07740301	3 x 0,14	0,11	3,3	4,0	13
07740401	4 x 0,14	0,11	3,6	5,4	15
07740501	5 x 0,14	0,11	3,8	6,7	18
07740701	7 x 0,14	0,11	4,4	9,4	24
07741001	10 x 0,14	0,11	5,1	13,4	30
07741201	12 x 0,14	0,11	5,2	16,1	34
07741401	14 x 0,14	0,11	5,5	18,8	38
07741801	18 x 0,14	0,11	6,0	24,2	48
07742501	25 x 0,14	0,11	7,1	33,6	63
07743201	32 x 0,14	0,11	7,6	43,0	78
07740202	2 x 0,25	0,11	3,5	4,8	15
07740302	3 x 0,25	0,11	3,7	7,2	18
07740402	4 x 0,25	0,11	3,9	9,6	21
07740502	5 x 0,25	0,11	4,2	12,0	25
07740702	7 x 0,25	0,11	4,9	16,8	34
07741002	10 x 0,25	0,11	5,7	24,0	43

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
07741202	12 x 0,25	0,11	5,8	28,8	49
07741402	14 x 0,25	0,11	6,1	33,6	56
07741802	18 x 0,25	0,11	6,8	43,2	71
07742502	25 x 0,25	0,11	8,1	60,0	94
07743202	32 x 0,25	0,11	8,8	76,8	120
07740203	2 x 0,34	0,11	3,7	6,5	17
07740303	3 x 0,34	0,11	3,9	9,8	21
07740403	4 x 0,34	0,11	4,2	13,1	25
07740503	5 x 0,34	0,11	4,5	16,3	30
07740703	7 x 0,34	0,11	5,2	22,8	41
07741003	10 x 0,34	0,11	6,1	32,6	52
07741203	12 x 0,34	0,11	6,3	39,2	60
07741403	14 x 0,34	0,11	6,6	45,7	69
07741803	18 x 0,34	0,11	7,3	58,8	87
07742503	25 x 0,34	0,11	8,9	81,6	119
07743203	32 x 0,34	0,11	9,5	104,4	149

Other dimensions and colours are possible on request.



On request also  
possible in dimensions  
**0,50 mm<sup>2</sup>**  
and  
**0,75 mm<sup>2</sup>!**