

## S 180 HT Continuously flexible high temperature control cable with numbered cores and Besilen® outer sheath



### Construction:

<b>Conductor:</b>	tinned copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 6
<b>Insulation:</b>	FEP
<b>Colour code:</b>	black cores with consecutive numbers acc. to EN 50334; green-yellow earth wire from 3 cores
<b>Stranding:</b>	specially adjusted layering with non-woven tape over each layer
<b>Wrapping:</b>	tape
<b>Sheath material:</b>	special Besilen®
<b>Sheath colour:</b>	grey (similar RAL 7000)

### Outstanding features:

- extreme temperature resistance
- high notch resistance
- very good flexibility
- EAC approval

### Technical data:

<b>Nominal voltage:</b>	U <sub>0</sub> /U 0,6/1 kV
<b>Testing voltage U:</b>	4000 V acc. to EN 50264
<b>Min. bending radius</b> <i>continuously flexible:</i>	10 x d
<b>Temperature range</b> <i>fixed laying:</i> <i>flexible application:</i> <i>short-time use:</i>	-25/+180 °C -25/+180 °C +200 °C
<b>Fire performance:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
<b>Flexibility:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17

B  
25

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
31800315	3 x 1,50	0,16	7,7	43,2	94
31800415	4 x 1,50	0,16	8,3	57,6	116
31800515	5 x 1,50	0,16	9,2	72,0	147
31800715	7 x 1,50	0,16	10,6	100,8	200
31800325	3 x 2,50	0,16	9,4	72,0	144
31800425	4 x 2,50	0,16	10,1	96,0	177
31800525	5 x 2,50	0,16	11,5	120,0	228
31800725	7 x 2,50	0,16	13,5	168,0	320
31800440	4 x 4,00	0,16	12,1	153,6	265
31800540	5 x 4,00	0,16	13,4	192,0	333
31800740	7 x 4,00	0,16	15,9	268,8	469
31800460	4 x 6,00	0,21	14,6	230,4	408
31800560	5 x 6,00	0,21	16,4	288,0	495
31800760	7 x 6,00	0,21	19,4	403,2	697
31800461	4 x 10,0	0,21	17,0	384,0	609
31800561	5 x 10,0	0,21	18,9	480,0	745
31800462	4 x 16,0	0,21	20,7	614,4	912
31800562	5 x 16,0	0,21	23,2	768,0	1146
31800463	4 x 25,0	0,21	24,0	960,0	1312
31800464	4 x 35,0	0,21	28,2	1344,0	1800

Other dimensions and colours are possible on request.



**Application:**  
for use  
in cable tracks  
with extremely  
ambient temperature  
like for example  
in steel industry!