

Servo Motor Cables

SL 813 C

PUR motor connection cable with PVC cores and overall copper screen 0.6/1 kV

suitable for
cable tracks

SAB Servo

0415 4 x 1,5 mm² SL 813 C 0,6/1 kV **DESINA** CE



Marking for SL 813 C 08130415:

SAB BRÖCKSKES · D-VIERSEN · 08130415 4 x 1,5 mm² SL 813 C 0,6/1 kV **DESINA** CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, VDE 0295, class 6
Insulation:	PVC, TI2 acc. to EN 50363-3 + VDE 0207-363-3
Colour code:	black cores with consecutive numbers acc. to EN 50334 + VDE 0293-334 and a green-yellow earth wire
Stranding:	in layers
Inner sheath:	PVC, TM2 acc. to EN 50363-4-1 + VDE 0207-363-4-1
Screen:	tinned copper braiding
Wrapping:	non-woven tape
Sheath material:	PUR, TPU acc. to EN 50363-10-2 + VDE 0207-363-10-2 with mat surface
Sheath colour:	orange (RAL 2003)

Technical data:

Nominal voltage:	U ₀ /U 0.6/1 kV
Testing voltage:	core/core 4000 V core/screen 4000 V
Min. bending radius <i>fixed laying:</i> <i>flexible application:</i> <i>continuously flexible:</i>	5 x d 10 x d 12 x d
Radiation resistance:	5 x 10 ⁷ cJ/kg
Temperature range <i>fixed laying:</i> <i>flexible application:</i>	-40/+70 °C +5/+70 °C
Oil resistance:	very good - TPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Absence of harmful substances:	acc. to RoHS directive of the European Union, see chapter N „Technical data“

Outstanding features:



- very good EMC characteristics
- suitable for cable tracks
- flexible
- rugged sheath
- oil resistant
- **DESINA®** colours (see page C/4)



for DNC motors
on frequency converters

C
7

item no.	no. of cores x cross section n x mm ²	AWG	largest single wire ø mm	outer-ø ± 5 % mm	copper figure kg/km	cable weight ≈ kg/km
08130415	4 x 1,50	16 / 4c	0,16	12,4	113,8	228
08130425	4 x 2,50	14 / 4c	0,16	15,4	165,9	345
08130440	4 x 4,00	12 / 4c	0,16	17,0	257,3	449
08130460	4 x 6,00	10 / 4c	0,21	19,2	346,3	594
08130470	4 x 10,00	8 / 4c	0,21	23,0	524,5	877
08130480	4 x 16,00	6 / 4c	0,21	26,4	777,0	1242
08130490	4 x 25,00	4 / 4c	0,21	30,7	1156,8	1763
08130495	4 x 35,00	2 / 4c	0,21	34,0	1574,3	2258
08130496	4 x 50,00	1 / 4c	0,31	39,3	2177,9	3076
08130515	5 x 1,50	16 / 5c	0,16	13,7	139,4	286
08130525	5 x 2,50	14 / 5c	0,16	16,7	222,8	420
08130540	5 x 4,00	12 / 5c	0,16	18,7	306,5	575
08130560	5 x 6,00	10 / 5c	0,21	20,8	422,1	733
08130570	5 x 10,00	8 / 5c	0,21	25,3	638,2	1097
08130580	5 x 16,00	6 / 5c	0,21	28,7	955,6	1524
08130590	5 x 25,00	4 / 5c	0,21	33,4	1427,1	2172
08130595	5 x 35,00	2 / 5c	0,21	37,4	1927,5	2748

Other dimensions and colours are possible on request.

Note: DESINA® is a registered trademark of the German Machine Tool Builders' Association.



www.sab-cable.com