

INDUSTRIAL ETHERNET CABLES PROFINET



S PN 667 Profinet type C, continuously flexible with UL recognition, CSA approval



21198 80°C 300V CSA AWM I/II A/B 80°C 300V FT2

Marking for S PN 667:

SAB BRÖCKSKES · D-VIERSEN · S PN 667 Industrial Ethernet FC Cat 5 Typ C 2x2x22AWG AWM Style 21198 80°C 300V CSA AWM I/II A/B 80°C 300V FT2

Construction:

Conductor:	tinned copper strands, 7 wires
Insulation:	special polymer
Colour code:	blue, yellow, white, orange
Stranding:	in layers
Wrapping:	PETP foil
Inner sheath:	thermoplastic material
Wrapping:	alu foil
Screen:	tinned copper braiding
Wrapping:	non-woven tape
Sheath material:	PUR
Sheath colour:	green (similar RAL 6018)

Technical data:

Peak operating voltage VDE:	max. 350 V
Voltage UL/CSA:	300 V
Testing voltage:	core/core 1500 V core/screen 1200 V
Min. bending radius	
<i>fixed laying:</i>	5 x d
<i>flexible application:</i>	10 x d
<i>continuously flexible:</i>	15 x d
Temperature range	UL/CSA: up to +80 °C
<i>fixed laying:</i>	-40/+70 °C
<i>flexible application:</i>	-40/+70 °C
Halogen-free:	acc. to DIN VDE 0472 part 815 + IEC 60754-1
Characteristic impedance:	100Ω ± 5Ω, accomplishes the electrical and transmission requirements with high frequency acc. to EN 50288-2-2 (CAT 5 acc. to EN 50173-1)
Oil resistance:	TMPU acc. to DIN VDE 0282 part 10 + HD 22.10
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/17

**E
35**

item no.	type	no. of cores	cross section AWG	core-ø max. mm	outer-ø mm	copper figure kg/km	cable weight ≈kg/km	ohmic resistance at 20°C acc. to VDE 0812 max.Ω/km
06672202	S PN 667	4	22	1,55	6,5 ± 0,2	33,8	60	58,8

Other dimensions and colours are possible on request.

For extreme bending stress - conductor construction 19 wires:

item no.	type	no. of cores	cross section AWG	core-ø max. mm	outer-ø mm	copper figure kg/km	cable weight ≈kg/km	ohmic resistance at 20°C acc. to VDE 0812 max.Ω/km
06679001	S PN 667	4	22	1,55	6,5 ± 0,2	33,8	58	58,8

Other dimensions and colours are possible on request.



short
assembling time by
„Fast Connect“
construction
(7 wires)