


## DR 717 P Highflex

BRÖCKSKES · D-VIERSEN · DR 717 P Highflex 4 G 2,5 mm<sup>2</sup> CE



Marking for DR 717 P Highflex 07170425:

SAB BRÖCKSKES · D-VIERSEN · DR 717 P Highflex 4 G 2,5 mm<sup>2</sup> CE

### Construction:

<b>Conductor:</b>	bare copper strands acc. to IEC 60228 EN 60228, VDE 0295, class 5
<b>Insulation:</b>	special polymer
<b>Colour code:</b>	coloured acc. to HD 308 (VDE 0293 part 308); from 6 cores black cores with consecutive numbers acc. to EN 50334; green-yellow earth wire from 3 cores <i>DMX-bus:</i> white/brown, green/yellow <i>IE Cat 5:</i> white-blue/blue, white-orange/orange, white-green/green, white-brown/brown
<b>Stranding:</b>	specially adjusted layering around central suspension unit
<b>Inner sheath:</b>	PUR
<b>Supporting screen:</b>	high-tech yarn
<b>Sheath material:</b>	PUR
<b>Sheath colour:</b>	black (RAL 9005)

### Outstanding features:

- reeling length up to 60 m
- extrem highly winding and unwinding strength
- corresponds to low voltage guideline 73/23/EWG CE
- small outer diameter
- small cable weight
- EAC approval

### Application:

- The DR 717 P Highflex is used for spring cables reels on stages and theatres

### Technical Data:

<b>Nominal voltage:</b>	U <sub>0</sub> /U 300/500 V (supply conductors)	
<b>Peak operating voltage:</b>	<i>item no. 07179001:</i> max. 500 V (DMX-bus) <i>item no. 07179002:</i> max. 125 V (IE Cat 5)	
<b>Testing voltage:</b>	core/core 2000 V	
<b>Current-carrying capacity:</b>	acc. to DIN VDE 0298-4, see page N/36 + N/37	
<b>Min. bending radius:</b>		
<i>for laying and installation (fixed laying):</i>	≤ 12 mm 3 x d / >12 mm 4 x d	
<i>for repeated winding action (flexible):</i>	6 x d	
<i>guided on deflection pulleys (flexible):</i>	7,5 x d	
<b>Temperature range</b>	<i>item no. 07179001</i>	<i>item no. 07179002</i>
<i>with installation:</i>		
<i>fixed laying:</i>	-50/+90 °C	-40/+70 °C
<i>flexible application:</i>	-40/+90 °C	-40/+70 °C
<b>Halogen-free:</b>	acc. to DIN VDE 0472 part 815 + IEC 60754-1	
<b>Oil resistance:</b>	very good - TMPU acc. to DIN VDE 0282 part 10 + HD 22.10	
<b>Chemical resistance:</b>	good against acids, alkalines, solvents, hydraulic liquids, etc.	
<b>Fire performance:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 and EN 60332-1-2	
<b>Sunlight resistance:</b>	very good - enhanced due to black sheath colour	
<b>Tensile strength:</b>	with reference to DIN VDE 0298-3 section 7.1	
<b>Mechanical characteristics:</b>	the main mechanical characteristics accomplished by the PUR outer sheath are: - high tensile strength - high tear strength - high abrasion resistance - high notch resistance	
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17	

item no.	no. of cores x cross section n x mm <sup>2</sup>	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km	tensile strength max. N	min breaking load of suspension unit N
07170425	4 G 2,50	9,7	96,0	157	150	1345
07170440	4 G 4,00	11,7	153,6	239	240	1690
07171440	14 G 4,00	20,9	537,6	739	840	3200
07172040	20 G 4,00	23,3	768,0	1021	1200	3700
07172540	25 G 4,00	28,3	960,0	1318	1500	4200
07170460	4 G 6,00	13,4	230,4	333	360	1860
07171360	13 G 6,00	24,3	748,8	1013	1170	3400
07171860	18 G 6,00	25,7	1036,8	1306	1620	6000
07170470	4 G 10,0	17,1	384,0	559	600	2300
07170480	4 G 16,0	21,3	614,4	864	960	2800
07179001	14 G 4,00 + 2 x (2 x 0,25)C	22,4	575,4	794	840	2500
07179002	5 G 16,0 + 4 x 2 x 0,14	26,4	791,6	1163	1200	3000
07179013	25 G 4,00	min. 25,0 max. 28,0	960,0	1290	1500	2600

Other dimensions and colours are possible on request.

Please mention the required winding length when placing the order.

**Note: Please pay attention to the installation instructions on page N/29**