

## N2GFA/2GFA Besilen® insulated wire acc. to DIN VDE 0250



### Construction:

<b>Conductor:</b>	solid tinned copper wire acc. to IEC 60228, EN 60228, VDE 0295, class 1
<b>Insulation:</b>	Besilen® EI2 acc. to DIN EN 50363-1

### Outstanding features:

- ▶ halogen-free
- ▶ 0,75 mm<sup>2</sup> DIN VDE standardized
- ▶ flexible at low temperatures
- ▶ heat resistant
- ▶ EAC approval

### Technical data:

<b>Nominal voltage:</b>	U <sub>0</sub> /U 300/300 V
<b>Testing voltage U:</b>	2000 V
<b>Min. bending radius:</b>	7,5 x d
<b>Radiation resistance:</b>	2 x 10 <sup>7</sup> cJ/kg
<b>Temperature range</b>	
<i>fixed laying:</i>	-40/+180 °C
<i>flexible application:</i>	-25/+180 °C
<i>short-time use:</i>	+250 °C
<b>Halogen-free:</b>	acc. to DIN VDE 0472 part 815 + IEC 60754-1
<b>Fire performance:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
<b>Corrosiveness of conflagration gases:</b>	IEC 60754-2 + EN 50267-2-2 + VDE 0482 part 267-2-2 - no development of corrosive conflagration gases
<b>Chem. resistance:</b>	see page N/11
<b>Weather resistance:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17

item no.	nominal cross section mm <sup>2</sup>	nominal wire-ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
0157005...*	0,50	0,80	2,1	4,8	9
0151007...*	0,75**	0,98	2,2	7,2	11
0157010...*	1,00	1,13	2,4	9,6	14
0157015...*	1,50	1,38	2,8	14,4	21
0157025...*	2,50	1,78	3,4	24,0	33

Other dimensions and colours are possible on request.

#### \* Colour code for single conductors:

...0 = green-yellow	...4 = grey
...1 = blue	...5 = white
...2 = black	...6 = reddish brown
...3 = brown	...7 = red
	...9 = nature

\*\* N2GFA 0,75 mm<sup>2</sup> according to DIN VDE 0250 part 502. Other cross sections with reference to DIN VDE 0250 part 502.