

HARNESSED CABLES

HARNESSED COAX CABLE

with high frequency plug connectors



DIFFERENT PLUG CONNECTORS FOR HIGH FREQUENCY APPLICATIONS

Besides cable harnesses with BNC plug connectors, SAB BRÖCKSKES offers further harnesses for high frequency applications for example coax cables with UHF-, mini-UHF or SMB connectors. We don't have a standard product range but special products for individual application ranges. These special applications are for example the requirements on temperature or flexibility.

CABLE CONSTRUCTION

conductor:	silver-plated copper strands 0,55 mm ²
core insulation:	polymer
screen:	silver-plated copper braiding
outer sheath:	special material
sheath colour:	black (RAL 9005)

TECHNICAL DATA

temperature range	
flexible application:	-40°C/+125°C
fixed laying:	-50°C/+125°C
short-time use:	+150°C
special feature:	silicone free, 75 Ω

Among others the following cable types belong to our delivery programme:

- ✓ low-noise cable
- ✓ RG 316
- ✓ RG 58
- ✓ RG 179
- ✓ coax cables with 50 Ω or 75 Ω
- ✓ cables with heat resistant, flexible outer sheath up to +150°C

Please choose from the following plug connectors:

- UHF plug connector
- mini UHF plug connector
- MMCX plug connector
- SMB plug connector
- ...