



### Construction:

Conductor:	copper strands acc. to IEC 60228
Insulation:	TPE
Colour code:	acc. to specification
Sheath material:	PUR, TPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Sheath colour:	black (RAL 9005)

item no.	dimension mm <sup>2</sup>	outer-ø ≈ mm
0795-9035	(2 x 0,5) D + (2 x 0,5) D	8,8
0726-0033	(2 x 0,5) D + 2 x 0,5	8,2
0796-9101	(3 x 1,0) D + (2 x 1,0) D + 1 x 1,0	10,4
0726-0035	4 x (2 x 0,50) D + 1 x 0,50	9,6
0726-0036	6 x 0,75 + (3 x 0,75) D	9,8
0726-0037	2 x (2 x 0,75) D + (3 x 0,75) D	10,3
0726-0038	1 x (2 x 0,50) D + 7 x 1,0	9,1

Other dimensions and colours are possible on request.

### Technical Data:

PWIS uncritical	Temperature range	Min. bending radius	Absence of harmful substances
all our robot cables are free of paint-wetting interfering substances	flexible application: -40/+90 °C	recommended: 10 x d	acc. to RoHS directive of the European Union



**Further KSR cables  
on request!**

