

# ACCESSORIES

clamp screw connection made of stainless steel with clamping cone PTFE

MTE ø mm	thread	width across flat	item no.	clamping cone in exchange item no.
1,0	M 6 x 1	10	T025-050-911	T025-050-912
1,5	M 6 x 1	10	T025-041-015	T025-050-913
1,5	M 8 x 1	10	T025-044-648	T025-048-577
1,5	M 8 x 1,25	10	T025-041-016	T025-041-402
2,0	M 8 x 1	10	T025-046-947	on request
3,0	M 8 x 1	10	T025-044-649	T025-048-578
3,0	M 8 x 1,25	10	T025-041-017	T025-041-403

pressure resistance for clamp screw connection  
with clamping cone PTFE: up to approx. 10 bar at room temperature  
max. application up to +200°C



clamp screw connection made of stainless steel with clamping cone stainless steel

MTE ø mm	thread	width across flat	item no.	clamping cone in exchange item no.
1,0	M 6 x 1	10	T025-048-328	T025-048-329
1,0	M 8 x 1	10	T025-046-946	T025-048-329
1,5	M 6 x 1	10	T025-041-404	T025-050-914
1,5	M 8 x 1	10	T025-044-647	T025-049-313
1,5	M 8 x 1,25	10	T025-041-019	T025-049-313
2,0	M 8 x 1	10	T025-046-945	T025-048-323
2,0	M 12 x 1,5	17	T025-048-324	T025-048-325
2,0	M 14 x 1,5	17	T025-048-326	T025-048-327
3,0	M 8 x 1	10	T025-044-646	T025-049-150
3,0	M 8 x 1,25	10	T025-041-018	T025-049-150

Pressure resistance for clamp screw connection  
with clamping cone stainless steel:  
up to approx. 200 bar at room temperature  
max. application up to +600°C



Also  
inch threads  
available.

Other dimension are possible on request!  
Each clamp screw connection includes a clamping cone in delivery.