

ACCESSORIES

Thermo plug

Standard thermo plug up to max. 200 °C	
item no.	min.t/c type
T 021-007-056	J (Fe-CuNi)
T 021-007-057	K (NiCr-Ni)


Standard thermo socket up to max. 200 °C	
item no.	min.t/c type
T 021-007-104	J (Fe-CuNi)
T 021-000-679	K (NiCr-Ni)

Miniature thermo plug up to max. 200 °C	
item no.	min.t/c type
T 021-007-071	J (Fe-CuNi)
T 021-007-072	K (NiCr-Ni)

High-temp. thermo plug up to max. 350 °C	
item no.	min.t/c type
T 021-007-064	J (Fe-CuNi)
T 021-007-065	K (NiCr-Ni)

High-temp. thermo socket up to max. 350 °C	
item no.	min.t/c type
T 021-007-111	J (Fe-CuNi)
T 021-007-112	K (NiCr-Ni)

Miniature thermo socket up to max. 200 °C	
item no.	min.t/c type
T 021-007-118	J (Fe-CuNi)
T 021-007-119	K (NiCr-Ni)




Cable fixing for:

Standard and high temp. plug
item no.
T 021-007-035

Miniature plug
item no.
T 021-007-041

Locking plate
item no.
T 021-029-182



Lemo socket for mineral insulated thermocouples and resistance thermometers

2-pole up to max. 200 °C		
item no.	size	outer-ø
T 021-011-146	0	0,64
T 021-011-147	0	1,0
T 021-009-083	1	1,5
T 021-000-600	1	3,0
T 021-011-149	1	4,5
T 021-011-152	2	6,0

4-pole up to max. 200 °C		
item no.	size	outer-ø
T 021-011-148	0	1,64
T 021-000-599	0	1,0
T 021-011-150	1	1,5
T 021-011-151	1	3,0
T 021-000-677	1	4,5
T 021-000-678	2	6,0



Lemo plug for cable connection

2-pole up to max. 200 °C		
item no.	size	outer-ø *
T 021-011-153	0	3,2
T 021-011-154	1	3,2
T 021-000-594	1	4,7
T 021-011-156	2	3,2
T 021-000-596	2	4,7
T 021-000-597	2	6,4

4-pole up to max. 200 °C		
item no.	size	outer-ø *
T 021-008-967	0	3,2
T 021-011-155	1	3,2
T 021-000-595	1	4,7
T 021-011-157	2	3,2
T 021-011-158	2	4,7
T 021-000-598	2	6,4



*outer-ø of cable

*outer-ø of cable

ACCESSORIES

Clamp screw connection made of steel 1.0718 for...

min.t/c ø mm	thread	with pressure ring made of PTFE item no.
1,5	M 8 x 1	T 025-007-148
2,0	M 8 x 1	T 025-007-151
3,0	M 8 x 1	T 025-000-681
4,5	G 1/4 A	T 025-007-157
6,0	G 1/4 A	T 025-000-685

Clamp screw connections made of steel 1.0718 for...

min.t/c ø mm	thread	with tapered ring made of stainless steel 1.4571 item no.
1,5	M 8 x 1	T 025-007-147
2,0	M 8 x 1	T 025-007-150
3,0	M 8 x 1	T 025-000-680
4,5	G 1/4 A	T 025-007-156
6,0	G 1/4 A	T 025-000-684



Clamp screw connections made of stainless steel 1.4571 for...

min.t/c ø mm	thread	with pressure ring made of PTFE item no.
1,5	M 8 x 1	T 025-007-146
2,0	M 8 x 1	T 025-007-149
3,0	M 8 x 1	T 025-007-153
4,5	G 1/4 A	T 025-007-155
6,0	G 1/4 A	T 025-007-160

Note:

Clamp screw connections with a thrust collar made of PTFE are appropriate for temp. up to +200°C and for pressures up to 10 bar. Later loosening and moving is possible.

Clamp screw connections made of stainless steel 1.4571 for...

min.t/c ø mm	thread	with tapered ring made of stainless steel 1.4571 item no.
1,5	M 8 x 1	T 025-007-145
3,0	M 8 x 1	T 025-007-152
4,5	G 1/4 A	T 025-007-154
6,0	G 1/4 A	T 025-007-159

Clamp screw connections with a tapered ring made of steel or stainless steel are appropriate for temp. above + 200 °C and for pressures up to 40 bar. By tightening the screw connection, the tapered ring is fixed on the tube and can't be loosened anymore. Therefore, later loosening isn't possible at all.

Please note that not all types are available from stock and that there are possibly min. order quantities!