

Halogen-free Cables

SABIX® BL 412 C FRNC


SABIX® BL-Line Power - flexible power cable
with overall copper screen 0.6/1 kV

0.6/1 kV



12 x 1,5mm² - IEC 60332-3-22 - 0,6/1kV

DNV CE



Marking for SABIX® BL 412 C FRNC 6412121:

SAB BRÖCKSKES · D-VIERSEN · SABIX® BL 412 C FRNC 12 x 1,5mm² - IEC 60332-3-22 - 0,6/1kV DNV CE and current meter marking

Construction:

| | |
|-----------------------|--|
| Conductor: | tinned copper strands acc. to IEC 60228, VDE 0295, class 5 |
| Insulation: | special SABIX® |
| Colour code | black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334, green-yellow earth wire from 3 conductors |
| Stranding: | in layers |
| Screen: | tinned copper braiding |
| Sheath: | special SABIX® SHF 1 compound acc. to IEC 60092-360 |
| Sheath colour: | black (RAL 9005) |

Outstanding features:



- halogen-free
- asbestos-free
- good EMC characteristics
- no flame propagation
- flame retardant and self-extinguishing
- flexible
- for applications
acc. to Hong Kong Convention
ingredients tested acc. to the requirements
of the Hong Kong Convention (2009) of the IMO
- approvals:
DNV

Technical Data:

| | |
|--|--|
| Nominal voltage: | U ₀ /U 0,6/1 kV |
| Testing voltage: | core/core 4000 V core/screen 4000 V |
| Min. bending radius | |
| fixed laying: | 4 x d |
| flexible application: | 6 x d |
| Temperature range | |
| fixed laying: | -40/+90 °C |
| flexible application: | -30/+90 °C |
| Halogen-free: | acc. to IEC 60754-1 + VDE 0482-754-1 |
| Fire performance: | no flame propagation acc. to IEC 60332-3-22 + VDE 0482-332-3-22 cat. A. Flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2 |
| Corrosiveness of conflagration gases: | in compliance with IEC 60754-2 + VDE 0482-754-2 - no development of corrosive conflagration gases |
| Smoke density: | acc. to IEC 61034 + VDE 0482-1034 |
| Flexibility: | very good |
| Absence of harmful substances: | acc. to RoHS directive of the European Union, see chapter N „Technical data“ |

A

59

Possible on request:



- bare copper strands
- alternative colour code
and sheath colour

| item no. | no. of cores x cross section n x mm ² | outer-ø ± 5% mm | copper figure kg/km | cable weight ≈ kg/km |
|----------|--|-----------------------|---------------------------|----------------------------|
| 64120215 | 2 x 1,50 | 9,4 | 55,0 | 123 |
| 64120315 | 3 x 1,50 | 9,9 | 72,2 | 140 |
| 64120415 | 4 x 1,50 | 10,9 | 105,2 | 181 |
| 64120515 | 5 x 1,50 | 12,1 | 126,2 | 226 |
| 64120715 | 7 x 1,50 | 13,1 | 160,4 | 275 |
| 64121015 | 10 x 1,50 | 17,0 | 253,8 | 417 |
| 64121215 | 12 x 1,50 | 17,5 | 283,2 | 465 |
| 64121415 | 14 x 1,50 | 18,3 | 313,1 | 516 |
| 64121815 | 18 x 1,50 | 20,4 | 384,8 | 654 |
| 64120225 | 2 x 2,50 | 10,2 | 77,1 | 155 |
| 64120325 | 3 x 2,50 | 11,0 | 119,6 | 190 |
| 64120425 | 4 x 2,50 | 12,1 | 150,2 | 236 |
| 64120525 | 5 x 2,50 | 13,2 | 179,6 | 286 |
| 64120725 | 7 x 2,50 | 14,7 | 253,9 | 376 |
| 64121025 | 10 x 2,50 | 18,6 | 351,9 | 525 |
| 64121225 | 12 x 2,50 | 19,1 | 411,8 | 600 |
| 64121425 | 14 x 2,50 | 20,2 | 461,2 | 683 |
| 64121825 | 18 x 2,50 | 22,6 | 572,7 | 865 |
| 64120240 | 2 x 4,00 | 12,6 | 131,3 | 238 |
| 64120340 | 3 x 4,00 | 13,3 | 174,9 | 277 |
| 64120440 | 4 x 4,00 | 14,9 | 239,6 | 361 |

| item no. | no. of cores x cross section n x mm ² | outer-ø ± 5% mm | copper figure kg/km | cable weight ≈ kg/km |
|----------|--|-----------------------|---------------------------|----------------------------|
| 64120540 | 5 x 4,00 | 16,3 | 290,3 | 443 |
| 64120740 | 7 x 4,00 | 17,9 | 379,7 | 566 |
| 64120260 | 2 x 6,00 | 13,8 | 175,0 | 303 |
| 64120360 | 3 x 6,00 | 14,8 | 258,8 | 368 |
| 64120460 | 4 x 6,00 | 16,1 | 328,4 | 466 |
| 64120560 | 5 x 6,00 | 17,9 | 398,9 | 567 |
| 64120760 | 7 x 6,00 | 19,6 | 527,5 | 723 |
| 64120361 | 3 x 10,0 | 17,7 | 398,7 | 542 |
| 64120461 | 4 x 10,0 | 19,5 | 508,1 | 732 |
| 64120561 | 5 x 10,0 | 21,4 | 618,8 | 853 |
| 64120362 | 3 x 16,0 | 20,9 | 598,7 | 768 |
| 64120462 | 4 x 16,0 | 23,0 | 755,9 | 992 |
| 64120562 | 5 x 16,0 | 25,6 | 938,8 | 1231 |
| 64120363 | 3 x 25,0 | 25,2 | 889,8 | 1126 |
| 64120463 | 4 x 25,0 | 27,8 | 1135,9 | 1465 |
| 64120563 | 5 x 25,0 | 30,8 | 1400,7 | 1805 |
| 64120364 | 3 x 35,0 | 28,4 | 1185,4 | 1508 |
| 64120464 | 4 x 35,0 | 31,3 | 1546,6 | 1978 |
| 64120365 | 3 x 50,0 | 32,0 | 1645,3 | 2039 |
| 64120465 | 4 x 50,0 | 35,2 | 2149,1 | 2678 |

Other dimensions and colours are possible on request.