

Industrial Ethernet Cables Profinet



PN 662 Profinet type B, for flexible applications

S PN 668 Profinet type C, continuously flexible

PN 663 Profinet type B, for flexible applications with UL recognition

S PN 669 Profinet type C, continuously flexible with UL recognition

0 C 2x2x22AWG AWM Style 21198 80° 300V



Marking for S PN 669 06692202:

SAB BRÜCKSKES · D-VIERSEN · S PN 669 Profinet CAT 5 Typ C 2x2x22AWG AWM Style 21198 80° 300V

Construction:	PN 662 Profinet type B <i>flexible</i>	S PN 668 Profinet type C <i>continuously flexible</i>	PN 663 Profinet type B <i>flexible</i>	S PN 669 Profinet type C <i>continuously flexible</i>
Dimension:	2 x 2 x 22 AWG			
Conductor:	tinned copper strands, fine wires with reference to VDE 0812	tinned copper strands, extra fine wires	tinned copper strands, fine wires with reference to VDE 0812	tinned copper strands, extra fine wires
Insulation:	PE, L/MD acc. to EN 50290-2-23	PE	PE, L/MD acc. to EN 50290-2-23	PE
Colour code:	blue, yellow, white, orange			
Stranding:	in layers			
Wrapping:	PETP foil			
Inner sheath:	thermoplastic material			
Screen:	alu foil and tinned copper braiding			
Wrapping:	---	non-woven tape	---	non-woven tape
Sheath material:	PVC	PUR	PVC	PUR
Sheath colour:	green (similar RAL 6018)			

Technical data:	PN 662 Profinet type B <i>flexible</i>	S PN 668 Profinet type C <i>continuously flexible</i>	PN 663 Profinet type B <i>flexible</i>	S PN 669 Profinet type C <i>continuously flexible</i>
Item number:	0662-2202	0668-2202	0663-2202	0669-2202
Peak operating voltage:	max. 350 V			
Voltage UL:	---		300 V	
Testing voltage				
core/core:	1500 V		2000 V	
core/screen:	1200 V		2000 V	
Min. bending radius				
fixed laying:	5 x d	5 x d	5 x d	5 x d
flexible application:	10 x d	10 x d	10 x d	10 x d
continuously flexible:		15 x d		15 x d
Temperature range VDE				
fixed laying:	-30/+70 °C	-40/+70 °C	UL: up to +80 °C -30/+70 °C	UL: up to +80 °C -30/+70 °C
flexible application:	-5/+70 °C	-30/+70 °C	-5/+70 °C	-20/+70 °C
Halogen-free:	---	acc. to IEC 60754-1 + VDE 0482-754-1	---	acc. to IEC 60754-1 + VDE 0482-754-1
Oil resistance:	acc. to internal standard, see chapter N „Technical data“	PUR, TPU acc. to EN 50363-10-2 + VDE 0207-363-10-2	acc. to internal standard, see chapter N „Technical data“	PUR, TPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Characteristic impedance:	100Ω ± 5Ω, fulfils the electrical and transmission requirements with high frequency acc. to EN 50288-2-2 + VDE 0819-2-2 (CAT 5 acc. to EN 50173-1)			
UL Style:	---		20601	21198
Absence of harmful substances:	acc. to RoHS directive of the European Union, see chapter N „Technical data“			

item no.	type	dimension	max. core-ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈kg/km	ohmic resistance at 20°C acc. to VDE 0812 max. Ω/km
06622202	PN 662	2 x 2 x 22 AWG	1,55	6,1	33,9	57	58,0
06682202	S PN 668	2 x 2 x 22 AWG	1,55	6,4	36,7	58	58,0
06632202	PN 663	2 x 2 x 22 AWG	1,55	6,5	36,2	66	58,0
06692202	S PN 669	2 x 2 x 22 AWG	1,55	6,9	36,7	69	58,0

Other dimensions and colours are possible on request.

Also possible as harnessed cable with M12 or RJ 45 plug!



www.sab-cable.com