



SafetyBUS p Cables

SBP 680 SafetyBUS p cable for fixed installation

S SBP 684 Move SafetyBUS p cable for flexible applications



BRÖCKSKES · D-VIERSEN · SafetyBUS p SBP 680 3x0,75mm² CE



Marking for SBP 680 06803754:

SAB BRÖCKSKES · D-VIERSEN · SafetyBUS p SBP 680 3x0,75mm² CE and current meter marking

· D-VIERSEN · SafetyBUS p MOVE S SBP 684 3x0,75mm² CE



Marking for S SBP 684 Move 06843754:

SAB BRÖCKSKES · D-VIERSEN · SafetyBUS p MOVE S SBP 684 3x0,75mm² CE and current meter marking

E
30

Construction:	SBP 680	S SBP 684 Move
Dimension:	3 x 0,75 mm ²	
Conductor:	bare copper strands acc. to VDE class 5	bare copper strands acc. to VDE class 6
Insulation:	acc. to EN 50290-2-23 + VDE 0819-103 (02Y11)	
Colour code:	acc. to DIN 47100	
Wrapping:	non-woven tape	
Screen:	---	tinned copper braiding
Wrapping:	non-woven tape	
Sheath material:	PUR	
Sheath colour:	signal yellow (RAL 1003)	

Technical data:	SBP 680	S SBP 684 Move
Item number:	0680-3754	0684-3754
Peak operating voltage:	max. 350 V	
Testing voltage		
core/core:	1500 V	
core/screen:	1200 V	
Min. bending radius		
fixed laying:	5 x d	5 x d
flexible application:	10 x d	10 x d
continuously flexible:		12 x d
Temperature range:	-40/+80 °C	
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1	
Oil resistance:	very good - PUR, TPU acc. to EN 50363-10-2 + VDE 0207-363-10-2	
Characteristic impedance at 1 MHz:	100 - 120 Ω	
Application in cable tracks:	not recommended	recommended
Continuously flexible application:	---	very good
Absence of harmful substances:	acc. to RoHS directive of the European Union, see chapter N „Technical data“	

item no.	type	dimension	outer-ø mm	copper figure kg/km	cable weight ≈kg/km
06803754	SBP 680	3 x 0,75 mm ²	7,8 ± 0,4	43,2	74
06843754	S SBP 684 Move	3 x 0,75 mm ²	7,8 ± 0,4	43,2	74

Other dimensions and colours are possible on request.